

LS

Lithica Stone

FLOOR & WALL · TROWEL APPLIED

An exposed aggregate system laid with steel and notched trowel, in two formulations that share one build: a water-free floor variant and a silicone-acrylic wall variant. Consumption follows the specified aggregate depth, so it is quoted by grade, not by area alone.

The build



Section shown from the substrate up. Coat order is fixed; consumption per coat is listed overleaf.

01 Primer
0.15 kg/m², 6.7 m² per kilogram.

02 Main aggregate
5-25 kg/m² depending on the grade specified.

03 Top coat
0.20 kg/m², sealer or hardener, specified separately.

WHY IT IS SPECIFIED

Exposed aggregate without a wet pour, and the only system in the range that takes the same aggregate up the wall as across the floor. The grade sets both texture and consumption, so specify the depth before the area.

ON QUOTING

The base build covers primer and aggregate. The top coat sealer or hardener is a separate item and should be stated as such on any bill of quantities.

Colour selection



A selection from thirty-three standard colours, shown unnamed — request the colour card for the reference numbers. Printed reproduction is indicative and should not be used for final selection.

Specification

APPLICATION	Steel trowel and notched trowel	CONSUMPTION	5–25 kg/m², following the specified depth
PRIMER	0.15 kg/m²	TOP COAT	0.20 kg/m²
GRADES	1–2 mm published; 2–4 mm and 3–5 mm to order	SEALER	Top coat sealer or hardener specified separately from the base build
SURFACES	Floor and wall — separate formulations	PERFORMANCE	Permeable, slip resistant, rated for vehicular traffic
SERVICE LIFE	Fifteen to twenty-five years	COLOURS	Thirty-three
CSI SECTION	32 14 00 · 32 14 13		

WARRANTY

One year standard.
Extended cover available.

ENQUIRIES

+632 8294 0478
pardue@techstone.com.ph
techstone.com.ph

OFFICE

Unit 103, Col. Efren R. Zaide Building
Bayani Road, Barangay Western Bicutan
Taguig City 1630, Philippines